

## § 15.256

resolution bandwidth spectrum analyzer. The center frequency must be stationary during the measurement interval, even if not stationary during normal operation (e.g., for frequency hopping devices).

(2) Peak transmitter conducted output power shall be measured with an RF detector that has a detection bandwidth that encompasses the 57–64 GHz band and that has a video bandwidth of at least 10 MHz. Measurement procedures that have been found to be acceptable to the Commission in accordance with § 2.947 of this chapter may be used to demonstrate compliance.

(3) For purposes of demonstrating compliance with this paragraph, corrections to the transmitter conducted output power may be made due to the antenna and circuit loss.

(f) *Frequency stability.* Fundamental emissions must be contained within the frequency bands specified in this section during all conditions of operation. Equipment is presumed to operate over the temperature range –20 to +50 degrees Celsius with an input voltage variation of 85% to 115% of rated input voltage, unless justification is presented to demonstrate otherwise.

(g) Regardless of the power density levels permitted under this section, devices operating under the provisions of this section are subject to the radio-frequency radiation exposure requirements specified in §§ 1.1307(b), 2.1091 and 2.1093 of this chapter, as appropriate. Applications for equipment authorization of devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

(h) Any transmitter that has received the necessary FCC equipment authorization under the rules of this chapter may be mounted in a group installation for simultaneous operation with one or more other transmitter(s) that have received the necessary FCC equipment authorization, without any additional equipment authorization. However, no transmitter operating under the provisions of this section may be equipped with external phase-locking

## 47 CFR Ch. I (10–1–14 Edition)

inputs that permit beam-forming arrays to be realized.

[63 FR 42279, Aug. 7, 1998, as amended at 66 FR 7409, Jan. 23, 2001; 68 FR 68547, Dec. 9, 2003; 78 FR 59850, Sept. 30, 2013]

### § 15.256 Operation of level probing radars within the bands 5.925–7.250 GHz, 24.05–29.00 GHz, and 75–85 GHz.

(a) Operation under this section is limited to level probing radar (LPR) devices.

(b) LPR devices operating under the provisions of this section shall utilize a dedicated or integrated transmit antenna, and the system shall be installed and maintained to ensure a vertically downward orientation of the transmit antenna's main beam.

(c) LPR devices operating under the provisions of this section shall be installed only at fixed locations. The LPR device shall not operate while being moved, or while inside a moving container.

(d) Hand-held applications are prohibited.

(e) Marketing to residential consumers is prohibited.

(f) The fundamental bandwidth of an LPR emission is defined as the width of the signal between two points, one below and one above the center frequency, outside of which all emissions are attenuated by at least 10 dB relative to the maximum transmitter output power when measured in an equivalent resolution bandwidth.

(1) The minimum fundamental emission bandwidth shall be 50 MHz for LPR operation under the provisions of this section.

(2) LPR devices operating under this section must confine their fundamental emission bandwidth within the 5.925–7.250 GHz, 24.05–29.00 GHz, and 75–85 GHz bands under all conditions of operation.

(g) *Fundamental emissions limits.* (1) All emission limits provided in this section are expressed in terms of Equivalent Isotropic Radiated Power (EIRP).

(2) The EIRP level is to be determined from the maximum measured power within a specified bandwidth.

(i) The EIRP in 1 MHz is computed from the maximum power level measured within any 1-MHz bandwidth using a power averaging detector;

(ii) The EIRP in 50 MHz is computed from the maximum power level measured with a peak detector in a 50-MHz bandwidth centered on the frequency at which the maximum average power level is realized and this 50 MHz bandwidth must be contained within the authorized operating bandwidth. For a RBW less than 50 MHz, the peak EIRP limit (in dBm) is reduced by  $20 \log(\text{RBW}/50)$  dB where RBW is the resolution bandwidth in megahertz. The RBW shall not be lower than 1 MHz or greater than 50 MHz. The video bandwidth of the measurement instrument shall not be less than the RBW. If the RBW is greater than 3 MHz, the application for certification filed shall contain a detailed description of the test procedure, calibration of the test setup, and the instrumentation employed in the testing.

(3) The EIRP limits for LPR operations in the bands authorized by this rule section are provided in Table 1. The emission limits in Table 1 are based on boresight measurements (*i.e.*, measurements performed within the main beam of an LPR antenna).

TABLE 1—LPR EIRP EMISSION LIMITS

Frequency band of operation (GHz)	Average emission limit (EIRP in dBm measured in 1 MHz)	Peak emission limit (EIRP in dBm measured in 50 MHz)
5.925–7.250 .....	–33	7
24.05–29.00 .....	–14	26
75–85 .....	–3	34

(h) *Unwanted emissions limits.* Unwanted emissions from LPR devices shall not exceed the general emission limit in §15.209 of this chapter.

(i) *Antenna beamwidth.* (A) LPR devices operating under the provisions of this section within the 5.925–7.250 GHz and 24.05–29.00 GHz bands must use an antenna with a –3 dB beamwidth no greater than 12 degrees.

(B) LPR devices operating under the provisions of this section within the 75–85 GHz band must use an antenna with a –3 dB beamwidth no greater than 8 degrees.

(j) *Antenna side lobe gain.* LPR devices operating under the provisions of this section must limit the side lobe antenna gain relative to the main beam gain for off-axis angles from the main beam of greater than 60 degrees to the levels provided in Table 2.

TABLE 2—ANTENNA SIDE LOBE GAIN LIMITS

Frequency range (GHz)	Antenna side lobe gain limit relative to main beam gain (dB)
5.925–7.250 .....	–22
24.05–29.00 .....	–27
75–85 .....	–38

(k) Emissions from digital circuitry used to enable the operation of the transmitter may comply with the limits in §15.209 of this chapter provided it can be clearly demonstrated that those emissions are due solely to emissions from digital circuitry contained within the transmitter and the emissions are not intended to be radiated from the transmitter’s antenna. Emissions from associated digital devices, as defined in §15.3(k) of this part, *e.g.*, emissions from digital circuitry used to control additional functions or capabilities other than the operation of the transmitter, are subject to the limits contained in subpart B, part 15 of this chapter. Emissions from these digital circuits shall not be employed in determining the –10 dB bandwidth of the fundamental emission or the frequency at which the highest emission level occurs.

(1) *Measurement procedures.* (1) Radiated measurements of the fundamental emission bandwidth and power shall be made with maximum main-beam coupling between the LPR and test antennas (boresight).

(2) Measurements of the unwanted emissions radiating from an LPR shall be made utilizing elevation and azimuth scans to determine the location at which the emissions are maximized.

(3) All emissions at and below 1,000 MHz except 9–90 kHz and 110–490 kHz bands are based on measurements employing a CISPR quasi-peak detector.

(4) The fundamental emission bandwidth measurement shall be made using a peak detector with a resolution

**§ 15.257**

**47 CFR Ch. I (10–1–14 Edition)**

bandwidth of 1 MHz and a video bandwidth of at least 3 MHz.

(5) The provisions in §15.35(b) and (c) of this part that require emissions to be averaged over a 100 millisecond period and that limits the peak power to 20 dB above the average limit do not apply to devices operating under paragraphs (a) through (1) of this section.

(6) Compliance measurements for minimum emission bandwidth of frequency-agile LPR devices shall be performed with any related frequency sweep, step, or hop function activated.

(7) Compliance measurements shall be made in accordance with the specific procedures published or otherwise authorized by the Commission.

[79 FR 12678, Mar. 6, 2014]

**§ 15.257 Operation within the band 92–95 GHz.**

(a) Operation of devices under the provisions of this section is limited to indoor use;

(1) Devices operating under the provisions of this section, by the nature of their design, must be capable of operation only indoors. The necessity to operate with a fixed indoor infrastructure, e.g., a transmitter that must be connected to the AC power lines, may be considered sufficient to demonstrate this.

(2) The use of outdoor mounted antennas, e.g., antennas mounted on the outside of a building or on a telephone pole, or any other outdoors infrastructure is prohibited.

(3) The emissions from equipment operated under this section shall not be intentionally directed outside of the building in which the equipment is located, such as through a window or a doorway.

(4) Devices operating under the provisions of this section shall bear the following or similar statement in a conspicuous location on the device or in the instruction manual supplied with the device: “This equipment may only be operated indoors. Operation outdoors is in violation of 47 U.S.C. 301 and could subject the operator to serious legal penalties.”

(b) Operation under the provisions of this section is not permitted on aircraft or satellites.

(c) Within the 92–95 GHz bands, the emission levels shall not exceed the following:

(1) The average power density of any emission, measured during the transmit interval, shall not exceed 9 uW/sq. cm, as measured at 3 meters from the radiating structure, and the peak power density of any emission shall not exceed 18 uW/sq. cm, as measured 3 meters from the radiating structure.

(2) Peak power density shall be measured with an RF detector that has a detection bandwidth that encompasses the band being used and has a video bandwidth of at least 10 MHz, or uses an equivalent measurement method.

(3) The average emission limits shall be calculated based on the measured peak levels, over the actual time period during which transmission occurs.

(d) Limits on spurious emissions:

(1) The power density of any emissions outside the band being used shall consist solely of spurious emissions.

(2) Radiated emissions below 40 GHz shall not exceed the general limits in §15.209.

(3) Between 40 GHz and 200 GHz, the level of these emissions shall not exceed 90 pW/cm<sup>2</sup> at a distance of 3 meters.

(4) The levels of the spurious emissions shall not exceed the level of the fundamental emission.

(e) The total peak transmitter output power shall not exceed 500 mW.

(f) Fundamental emissions must be contained within the frequency bands specified in this section during all conditions of operation. Equipment is presumed to operate over the temperature range –20 to +50 degrees Celsius with an input voltage variation of 85% to 115% of rated input voltage, unless justification is presented to demonstrate otherwise.

(g) Regardless of the maximum EIRP and maximum power density levels permitted under this section, devices operating under the provisions of this section are subject to the radio-frequency radiation exposure requirements specified in 47 CFR 1.1307(b), 2.1091, and 2.1093, as appropriate. Applications for equipment authorization of devices operating under this section must contain a statement confirming compliance with these requirements